

3G Active Call-Out DVR System



● Overview

This smart surveillance system optimizes the 3G Active Event Warning function. When an alarm is triggered, the security system will actively call out to your 3G mobile phone, so that you can quickly know what happened remotely by the live video alert. In addition, you can also call back to the 3G server to connect to the control software of the DVR system or speed dome camera for more live monitoring and control.

● Features

- Actively calls out to your 3G mobile phone when an event occurred
- Remote surveillance directly by calling to 3G server with 3G mobile phone
- No additional software installation to 3G mobile phone required
- 1 phone number assigned to avoid missed calls when an alarm is triggered (deputy)
- Secretary privilege assignment
- SMS message sending to 3G mobile phone after DVR or camera power failure
- Event notification via 3G network, Internet or PSTN
- Each RFID controller is unique and can't be duplicated.
- Setup and control of speed dome camera, PIR camera & DVR
- Easy installation without ruining the existing decoration
- Security service personnel replacement
- Detection activation log for all, Check in and out time records
- Compatible with home automation (HA) system





AVD714



4CH MPEG4 Network DVR (3G supported)

● Features

➤ MPEG4 DVR Technology

- MPEG4 Compression format providing crystal clear images with real time performance
- MPEG4 network transmitting format for a more fluent web transmission

➤ Supports Mobile Surveillance and 3G Call Out Function

- Motion or alarm trigger will send alerts with live video to the designated mobile phone

➤ Graphical & Multi-language OSD

➤ Remote Independent Operation

- Allows single-channel viewing of live displays without changing display settings on the licensed software AP provided

➤ Free Upgrade to Advanced Functions

- Allow you to upgrade DVR functions without any charges

➤ Multiplex Operation

- Allows live display, record, playback, backup, and network operations at the same time

➤ Excellent Image Quality and Performance

- The CIF image quality is excellent for clear and detailed image

➤ Intelligent Motion Trigger Recording

- R.E.T.R. (Remote Event Trigger Recording)
- Activates event recording automatically when alarm is triggered, and send alerts with images to the designated e-mails / FTP address
- Customizable security settings are achieved with the advanced motion detection, the scheduled motion detection recording (with 4 individually adjustable parameters), and the quick search function
- Supports pre-alarm recording (8MB)

➤ Backup Function

- Supports USB 2.0 flash drive, USB 2.0 portable drive, network & DVD writer backup

➤ Remote Surveillance

- Supports remote surveillance up to 5 users simultaneously with licensed software "Video Viewer" / Internet Explorer or Mozilla Firefox web browser / QuickTime player

➤ Covert Recording

- Blank screen replaces live displays to achieve covert recording

➤ A/V Support

- Supports 2 audio-in, 1 audio-out to record sounds
- Supports VGA output to monitor (optional)

➤ General

- LCD Display on the front panel
- Supports IR remote control
- System auto recovery after power failure
- Supports PTZ camera operations through RS-485, and PTZ Hot Point function
- Supports daylight saving function
- Supports manual / timer / motion / alarm / network recording
- Ensures the authentication of recorded images with watermark function
- Supports TCP/IP, PPPoE, DHCP and DDNS network connection



AVD714



4CH MPEG4 Network DVR (3G supported)

● Specifications

	AVD714
Video System	NTSC / PAL (auto detection)
Video Compression Format	MPEG4
Video Input	4 Channels (Composite video signal 1 Vp-p 75Ω BNC)
Video Loop Output	4 Channels (Composite video signal 1 Vp-p 75Ω BNC)
Video Output	Main Monitor Output: Composite video signal 1 Vp-p 75Ω BNC ; Call Monitor Output: Composite video signal 1 Vp-p 75Ω BNC
Maximum Recording Rate	Frame: 720×480 pixels with 30 IPS <NTSC> / 720×576 pixels with 25 IPS <PAL> CIF: 352×240 pixels with 120 IPS <NTSC> / 352×288 pixels with 100 IPS <PAL>
Adjustable Recording Speed	Frame: 30, 15, 7, 3 IPS <NTSC> / 25, 12, 6, 3 IPS <PAL> CIF: 120, 60, 30, 15 IPS <NTSC> / 100, 50, 25, 12 IPS <PAL>
Mobile Surveillance	YES
Multilingual OSD	YES
Image Quality Setting	Best, High, Normal, and Basic
Hard Disk Storage	Accommodates 2 HDDs
HDD Quick Cleaning	Quick cleans up the “index system” of the recorded files (750GB under 2 seconds)
Recording Mode	Manual / Timer / Motion / Alarm / Remote
Watermark	YES
Refresh Rate	120 IPS for NTSC / 100 IPS for PAL
Multiplex Operation	live display, record, playback, backup and network
Independent Remote Operation	Yes
Audio I/O	2 audio inputs, 1 audio outputs (Mono)
R.E.T.R. (Remote Event Trigger Recording)	YES
Motion Detection Area	16 × 12 grids per camera for all channels

	AVD714
Motion Detection Sensitivity	4 adjustable variables with precise calculation for motion detection
Pre-alarm Recording	YES (8 MB)
Backup Device	1. USB 2.0 flash drive; 2. Network; 3. DVD writer
USB Interface	front panel * 1
Web Transmitting Compression Format	MPEG4
Ethernet	10/100 Base-T. Supports remote control and live view via Ethernet
Web Interface	Licensed software "Video Viewer" / Internet Explorer or Mozilla Firefox web browser / QuickTime player
Remote Alarm Notification	Emails images, and uploads images to FTP site's specific account
Network Protocol	TCP/IP, PPPoE, DHCP and DDNS
IR Transmitter	YES
PTZ Control	YES
Dwell Time (Sequential Channel Switch)	Programmable with adjustable dwell time (2, 4, 8, 16 sec.)
Alarm I/O	4 inputs, 1 output
Picture Zoom	2X digital zoom
Key Lock	YES
Video Loss Detection	YES
Camera Title	Supports up to 6 letters
Video Adjustable	Hue / Color / Contrast / Brightness
Date Display Format	YY/MM/DD, DD/MM/YY, MM/DD/YY, and Off
Daylight Saving	YES
Power Source ($\pm 10\%$)	DC 19V
Power Consumption ($\pm 10\%$)	< 64 W
Operating Temperature	10°C ~ 40°C (50°F ~ 104°F)
Dimensions (mm)**	375(W) × 61(H) × 281(D)
System Recovery	System auto recovery after power failure
Optional Peripherals	VGA converter
3G (3rd Generation) Support	YES

*The specifications are subject to change without notice

** Dimensional tolerance: $\pm 5\text{mm}$

● Rear Panel

