

Features and Benefits

$\mathsf{Polycom}^{\mathbb{R}}\,\mathsf{HDX^{\mathsf{TM}}}$ Room Telepresence Series



Audio	Benefits
Polycom 22 kHz StereoSurround™	 2 channels of 22 kHz crystal clear audio
	 Superb clarity to hear the subtleties of every word
	 Easily decipher multiple, simultaneous conversations
	 Distinguish which side of the room people are talking from, just like a real meeting
Audio Error Concealment	 Eliminates audio drop-outs on noisy networks
	 Smooth, consistent verbal communications without interruptions
	 Corrects audio from any system seamlessly
	 Activates automatically, only when needed
Multiple Audio Inputs	 Audio inputs for PC (All HDX) aux audio or VCR/DVD (HDX 7000, 8000 & 9000)
Multiple Microphone Arrays	 Supports medium to large rooms with multiple microphone arrays (HDX 7000, 8000 & 9000)
Video	
True High Definition Video	 Natural high definition during video call and superb video at any data rate
	 Reduce the technology barriers by seeing people and content in HD resolution
	 1080p (starting from 1024 kbps)*
	 720p60 (from 832 kbps)* / 720p30 (from 512 kbps)
	 4C/SIF30 (from 128 kbps) 4C/SIF60 (from 512 kbps)*
Polycom EagleEye™ 1080 HD Camera	• 1080i/720p30/60
	• 1/3 2 MP CMOS Imager
	 70 deg FOV at min zoom
	10x optical zoom
Polycom EagleEye™ Camera	• 720p30/60
	• 72 degree field of view
	 270+ degree panning radius
	12X optical zoom
Polycom EagleEye™ View Camera	• 1080i/720p30/60
	 10 MP CMOS Imager
	Electronic PTZ
	• 55 degree field of view
	 4X digital zoom

Polycom Lost Packet Recovery™ (LPR)	Communications remain intact even on disruptive networks
	Smooth, continuous video without interruptions
	Maintain active face-to-face contact
	 Accomplish meeting objectives without worrying about
	the video integrity of public or private networks
	Activates automatically, only when needed
Dual Monitor Emulation	Most efficient use of a single display
	View near and far video windows at the same time
	 Alternate layout views supporting near end, far end and content in native aspect ratio and resolutions
Dedicated DVD/VCR Connection	Ability to use line level inputs for other devices
(HDX 7000, 8000 & 9000)	 Easily play movies/images during a video conference
	 Adds another dimension to the conference, making it
	like "being there"
	By setting it to "content" input see both the speaker and the DVDVCR image.
Additional HD Capable Video Source	the DVD/VCR imageSecondary HD video input allows for another HD
	camera, document camera or other HD device to be
	included in any video conference as a "People" or
	"Content" source.
Content Sharing	
People+Content™, H.239	Maintain eye-contact with far end - dual images allows
	far end to see presentation and speaker at the same time
	 People and Content both shared in High Definition at full-frame rates
	 Polycom People+Content or standards based H.239 ensures fully interoperability
People on Content™	 Unique feature allows users to become part of their
(HDX 8000 & 9000)	presentations
	 Using chroma-key technology, users can place themselves in front of the PC video input source.
	 Perfect for distance education and training
	Retain attention, increase productivity
Adjustable Bandwidth for Content	Flexibility to choose the amount of bandwidth to
Adjustable Bandwidth for Content	dedicate to Content or People based upon what is
	being shown
	 Options include 90% Content / 10% People; 50%
	Content / 50% People; 10% Content / 90% People
	System will automatically adjust bandwidth allocation when sharing content based upon content being shown.
	when sharing content based upon content being shownVery powerful for users who share a wide range of
	content during a video call
	User adjustable setting can be accessed both during a
	call and outside of a call



Harm Interfere	
User Interface Support for API Control Commands	Custom control touch panel integration including AMX®
(HDX 8000, 9000)	or Crestron [®] is made easy with extensive support for API command set
	 Integrator's Reference Manual for HDX Series details over 200 commands for special applications
	 Sample control templates are available for touch panel
	integration that provides basic functionality right out of the box
User Selectable Camera Icons	Use icons that represent your industryIntuitive icons match the input device
	Custom name gives the icon clear meaning
	 Selection – 5 libraries to choose from
	Decreases learning curve
Customizable Home Screen	Users have the ability to customize home screen to have a unified experience throughout an organization
Calendaring	 Invite people and video systems to a meeting through the integration of Microsoft Outlook™
	 The HDX UI has meeting information conveniently located on-screen to make joining a meeting easier
Platform Versatility	
Internal Multipoint Software	Optional upgrade easily done with a software key
(HDX 7000, 8000 & 9000)	 Conduct meetings beyond just point-to-point Increase productivity by including key people on the
	call
	 Adding sites during a call can lead to quick decision
	making
	 Supports up to 4 video calls in a single conference Polycom video systems are the most secure video
Secure Web	conferencing solutions in the industry
	 All access to the HDX system can be secured including accessing the HDX system via web-browser for secure
	system administration and application connectivity
Advanced Encryption Standard (AES)	 Communications are confidential and secure
	 Authentication by the National Institutes of Standards means it's credible
	Built-in, no extra hardware required
H.460 NAT/Firewall Traversal	Standards compliance for traversing NATs and Firewalls
	 Session border controller (VBP) is only needed at the central location and all VSX systems with H.460 can
	communicate through the single VBP
	Uses H.460.18 for signaling traversal and call
IP (H.323 or SIP), ISDN or Serial Connectivity	 establishment and H.460.19 for media traversal IP is standard and you choose the H.320 interface best
ii (iiiozo di dii), ioziv di donal donilodivity	for your application
	Choose the right option for your specific network connection.
	connection Supports UPnP and NAT for automatic setup of
	conferences conducted through firewalls



	 Wide range of IP QoS services to insure call quality and integrity
	 Optional H.320 interfaces include Quad BRI, PRI, V.35, RS-449 and RS-530 (HDX 8000 & 9000)
Multiple Use RS-232 Port (HDX 7000, 8000 & 9000)	 RS-232 port Integrate easily with control panels (HDX 8000 & 9000) or use for data pass-through for third-party devices.
Microsoft® OCS™ 2007 Integration	 Full integration with OCS allows endpoints to join "buddy" lists and participate in ad-hoc conferences One-click connectivity Presence capabilities allows users to see if video endpoints are currently in a call or available
Interoperability	orrapolitio and darrottely in a dail of available
Part of Polycom's Unified Collaborative Communications	 Remote management and scheduling through CMA 4000 or 5000 RMX Click & View™ offers a variety of layout templates for multipoint call right from the system's handheld remote
	 Play, stop, record, rewind and fast forward video recordings with the RSS 2000 using the HDX remote control
	 Expand the audience over audio and video with an RMX[™] bridge Video recording, streaming and archiving with the Polycom RSS 2000[™].
Standards-based	Solid, reliable platform
	 Qualified by independent test labs Interoperates with other standards-based systems in the industry
	 Easy to install even in a multi-vendor environment
Baseline Mode	 Set your system to baseline mode, H.261 and G.711, for maximum interoperability with legacy video conferencing systems Accessible via web, FTP or on-screen UI for easy access by the network administrator
	 Can be turned on and off as needed
Technical Documentation	
Award Winning Documentation	 Documentation set includes information about setting up, maintaining, and using the system Available at www.polycom.com/videodocumentation Searchable PDFs with colorful illustrations Administrators Guide, User's Guide, and Quick Tips available in most supported languages
Setup Sheets	 Easy-to-follow graphical instructions for setting up the system and peripherals Illustrations show both minimal and optional system configurations Shipped with the system for easy access
Administrator's Guide	Comprehensive information for configuring system,



including an explanation of each administrator setting

- Descriptions of system features and capabilities
- Back panel diagrams of all systems with explanations of each connector
- Instructions for using the web interface
- Quick Tips one-page document provides quick and easy reference for video conferencing tasks
- User's Guide covers everything you need to know



HDX 9000





User Documents